

# SA-4C

---



PIM-Guard® Four-Way Snap-in Stand-off Adapter has two slots for round member attachment and 3/8" holes for angle adapter integration. It includes four 3/4" holes for Snap-in hangers, supporting three 4-30mm or two 36-42mm cable stacks per hole

## Product Classification

<b>Product Type</b>	Adapter
<b>Product Brand</b>	PIM-Guard®
<b>Ordering Note</b>	ANDREW® standard product (Global)

## General Specifications

<b>Adapter Type</b>	Stand-off adapter
<b>Color</b>	Black
<b>Mounting</b>	3/4 in through hole   3/8 in through hole   Round member

## Dimensions

<b>Maximum Stack Height</b>	3
<b>Height</b>	54.61 mm   2.15 in
<b>Outside Width</b>	40.132 mm   1.58 in
<b>Outside Length</b>	86.36 mm   3.4 in

## Material Specifications

<b>Material Type</b>	Engineered plastic
----------------------	--------------------

## Mechanical Specifications

<b>Maximum Loading</b>	Double stack for hangers SSH-2630, SSH-3642   Triple stack for hangers SSH-411, SSH-1117
<b>Vibration Survival</b>	≥4 hours at resonant frequency

## Environmental Specifications

<b>Operating Temperature</b>	-40 °C to +85 °C (-40 °F to +185 °F)
<b>Environmental Strength Capability</b>	Double cable weight
<b>UV Resistance, minimum with no degradation</b>	≥1000 hours

# SA-4C

---

## Packaging and Weights

<b>Height, packed</b>	17 cm   6.693 in
<b>Width, packed</b>	13 cm   5.118 in
<b>Length, packed</b>	10 cm   3.937 in
<b>Packaging quantity</b>	10
<b>Weight, gross</b>	0.27 kg   0.595 lb

## \* Footnotes

**Maximum Stack Height** Fiber, Hybrid, Power