28B0-D3-A00D00-00 | CMC28



Empty CMC28 2000W HVAC Empty Outdoor Equipment Cabinet

The cabinet is designed to house rack mounted equipment. This includes DC power systems, Fiber storage/splice trays, cell site routers, batteries, and other rack mounted equipment. This cabinet provides mechanical and environmental protection for the equipment inside.

- Excellent Thermal Performance compatible with thermosiphon or HVAC
- Provides mounting space for power distribution, network servers, batteries, or other equipment.
- Front door compatible with Pad Lock.
- Provides flexible access for the cable entrances.
- Optional heater for cold environments.
- Provides 28RU of 19" or 23" Rack Space for Equipment
- Common parts available across the same platform.

Product Classification

Product Type Outdoor cabinet

Product Series CMC

General Specifications

Access Front door | Removable panel

Alarm Type Door alarm | HVAC alarms (including high temperature, failure) | S2 module, 20P or

standard and user defined alarms

Batteries Not included

Batteries Supported 9

Capacity 1000 W Heater

Color Gray

Cooling 3000W HVAC | 380 W/k Thermosiphon

Door SecurityQuarter turn lock, puck lock system for rear door | Swing handle, puck lock system for front

door

Mounting H-frame | Pad | Pole | Universal wall mount

Page 1 of 2



28B0-D3-A00D00-00 | CMC28

Noise Emission, maximum 65 dBA

Rack Type EIA 19 in | EIA 23 in

Rack Units 28

Dimensions

 Height
 1,447.8 mm | 57 in

 Width
 711.2 mm | 28 in

 Depth
 711.2 mm | 28 in

Electrical Specifications

Battery String Current, maximum 170 A-h @ -48 Vdc

Battery Strings, quantity 3 @ -48 Vdc

Cooling Capacity 3800 W

dc Distribution Type 19" or 23" Rack DC Distribution Panels or DIN Breakers

Voltage -48 Vdc

Material Specifications

Finish Powder coated | UV resistant

Material Type Aluminum

Environmental Specifications

Operating Temperature $-40 \,^{\circ}\text{C}$ to $+46 \,^{\circ}\text{C}$ (-40 $^{\circ}\text{F}$ to +115 $^{\circ}\text{F}$)

Storage Temperature $-40 \,^{\circ}\text{C}$ to $+70 \,^{\circ}\text{C}$ (-40 $^{\circ}\text{F}$ to +158 $^{\circ}\text{F}$)

Environmental Space UV resistant for outdoor

Qualification Standards IP55 | Telcordia GR-487

Thermal Compliance GR-487

Packaging and Weights

Weight, net 95.254 kg | 210 lb

Regulatory Compliance/Certifications

Agency Classification

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

