

FF-45C-R1



4-port sector antenna, 4x 617–894 MHz, 45° HPBW, 1x RET

- Narrow beamwidth capacity antenna for higher level of densification and enhanced data throughput
- High gain for maximum coverage

General Specifications

Antenna Type	Sector
Band	Single band
Color	Light Gray (RAL 7035)
Grounding Type	RF connector inner conductor and body grounded to reflector and mounting bracket
Performance Note	Outdoor usage
Radome Material	Fiberglass, UV resistant
Reflector Material	Aluminum
RF Connector Interface	4.3-10 Female
RF Connector Location	Bottom
RF Connector Quantity, high band	0
RF Connector Quantity, mid band	0
RF Connector Quantity, low band	4
RF Connector Quantity, total	4

Remote Electrical Tilt (RET) Information

RET Hardware	CommRET v2
RET Interface	8-pin DIN Female 8-pin DIN Male
RET Interface, quantity	1 female 1 male
Input Voltage	10–30 Vdc
Internal RET	Low band (1)
Power Consumption, active state, maximum	10 W
Power Consumption, idle state, maximum	2 W
Protocol	3GPP/AISG 2.0 (Single RET)

Dimensions

FF-45C-R1

Width	970 mm 38.189 in
Depth	235 mm 9.252 in
Length	2438 mm 95.984 in
Net Weight, without mounting kit	81.8 kg 180.338 lb

Array Layout

R1

R2

Array ID	Frequency (MHz)	RF Connector	RET (SRET)	AISG No.	AISG RET UID
R1	617-894	1 - 2	1	AISG1	CPxxxxxxxxxxxxR1
R2	617-894	3 - 4			

(Sizes of colored boxes are not true depictions of array sizes)

Port Configuration



Electrical Specifications

Impedance	50 ohm
Operating Frequency Band	617 – 894 MHz
Polarization	±45°
Total Input Power, maximum	600 W @ 50 °C

Electrical Specifications

Frequency Band, MHz	617–698	698–803	817–894
Gain, dBi	17.5	18	18.1

FF-45C-R1

Beamwidth, Horizontal, degrees	48	42	39
Beamwidth, Vertical, degrees	10.2	9.2	7.9
Beam Tilt, degrees	0–10	0–10	0–10
USLS (First Lobe), dB	18	19	17
Front-to-Back Ratio at 180°, dB	42	37	36
Isolation, Cross Polarization, dB	25	25	25
Isolation, Inter-band, dB	25	25	25
VSWR Return loss, dB	1.5 14.0	1.5 14.0	1.5 14.0
PIM, 3rd Order, 2 x 20 W, dBc	-150	-150	-150
Input Power per Port at 50°C, maximum, watts	250	250	250

Mechanical Specifications

Wind Loading @ Velocity, frontal	3,022.0 N @ 150 km/h (679.4 lbf @ 150 km/h)
Wind Loading @ Velocity, lateral	922.0 N @ 150 km/h (207.3 lbf @ 150 km/h)
Wind Loading @ Velocity, rear	3,022.0 N @ 150 km/h (679.4 lbf @ 150 km/h)
Wind Speed, maximum	241 km/h (150 mph)

Packaging and Weights

Width, packed	1122 mm 44.173 in
Depth, packed	575 mm 22.638 in
Length, packed	2689 mm 105.866 in
Weight, gross	124 kg 273.373 lb

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant



Included Products

BSAMNT-8	–	Wide Profile Antenna Down tilt Mounting Kit for 3.0 - 4.5 in (75 - 115mm) OD round members. Kit contains one scissor top bracket set and one bottom bracket set.
----------	---	--

FF-45C-R1

* Footnotes

Performance Note Severe environmental conditions may degrade optimum performance



BSAMNT-8



Wide Profile Antenna Down tilt Mounting Kit for 3.0 - 4.5 in (75 - 115mm) OD round members. Kit contains one scissor top bracket set and one bottom bracket set.

Product Classification

Product Type Downtilt mounting kit

General Specifications

Application Outdoor
Color Silver

Dimensions

Compatible Diameter, maximum 114.3 mm | 4.5 in
Compatible Diameter, minimum 61 mm | 2.402 in
Weight, net 6 kg | 13.228 lb

Material Specifications

Material Type Galvanized steel

Packaging and Weights

Included Brackets | Hardware
Packaging quantity 1
Weight, gross 6.2 kg | 13.669 lb

Regulatory Compliance/Certifications

Agency	Classification
CE	Compliant with the relevant CE product directives
CHINA-ROHS	Above maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant/Exempted
UK-ROHS	Compliant/Exempted

BSAMNT-8

