A-VF1-EXX3G

Base Product



PSC Cabinet Ericsson Fitout 3

PSC cabinet with internal racking to accommodate upto 6 BBU's and transmission. The following features are included in the cabinet:

- 6U Eltek PSU
- 6 No. 3kW Rectifiers
- 3 No. 100Ah Battery
- 2 No. 12-way DCDU for Ericsson Radios
- 6-way SPD Protected DCDU for Pole Mounted 4G Radios.

Product Classification

Regional Availability	EMEA		
Product Type	Outdoor cabinet		

General Specifications

Access	Front and rear door
Accessories	Cable plate External alarm connection Hangers In-ground root Plinth
Cabinet Type	Baseband cabinet Power cabinet Transmission cabinet
Cable Entry Location	Bottom
Color	Green (RAL 6009) Light Gray (RAL 7035) Others available at additional cost
Cooling	175 mm fan (1)
Door Security	Internal door contact for front door Swing handle with European profile cylinder for front door
Door Type, front	Key lock (includedl) Non-removable
Door, quantity	2
Front Door Type	Single hinged
Lock Type	Internal latch for rear door Key lock for front door
Mounting	In-ground root Plinth
Radios Included	None
Dimensions	
Height	1,721.866 mm 67.79 in
Width	822.96 mm 32.4 in

Page 1 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 12, 2025

A-VF1-EXX3G

Depth		599.948 mm	I	23.62 in

Material Specifications

FinishPowder coatedMaterial TypeGalvanized steel

Environmental Specifications

Qualification Standards IEC 60529, IP54

Packaging and Weights

Weight, net 399.996 kg | 881.84 lb

Page 2 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 12, 2025