## 1509874-002 | RMT2128-RF-14



# REGAL Complete RF Tap, 8-way, 1.2 GHz Full-Feature Equalizable, 14.5 dB nominal tap value, 12 A Power passing, narrow body

- \*Product complies with the Build America, Buy America Act (BABAA) requirements of the Infrastructure Investment and Jobs Act of 2021 (Pub. L. 117- 58, §§ 70901-70953), or is the subject of a waiver approved by the Secretary of Commerce or designee. Compliance requirements and waiver applicability vary based on government funding program. Check the laws and regulations for your specific program.
- Support DOCSIS® 3.1 expanded bandwidth up to1218 MHz
- Improve network performance with signal conditioning plug-ins
- High quality RF connection with auto-seize F-connectors
- Maintain existing Regal installed base with compatible faceplate upgrades
- Faceplate only options for cost effective upgrades to existing Regal deployments
- High level of network resilience with 6kV surge resistance on feederline and F-ports
- Maintain feederline RF and AC connections with faceplate removed with integrated bypass capability

### Product Classification

Regional Availability	Asia   Australia/New Zealand   EMEA   Latin America   North America
Product Type	RF tap
Product Series	REGAL
Government Requirements	Build America Buy America (BABA) compliant*
General Specifications	
Location of Manufacturing	Waived per BABA waiver for BEAD Program
Number of Ports	8
Dimensions	
Height	101.6 mm   4 in
Depth	76.2 mm   3 in
Length	95.25 mm   3.75 in
Electrical Specifications	
Bandwidth	5 – 1218 MHz MHz
Insertion Loss, tap, nominal	14.5 dB
Power Passing at 60/90V, maximum	12 A
Surge Protection, F port	6 kV Combination Wave

Page 1 of 2

©2025 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: April 30, 2025



## 1509874-002 | RMT2128-RF-14

#### 6 kV Combination Wave Surge Protection, input/output ports **Environmental Specifications Operating Temperature** -40 °C to +60 °C (-40 °F to +140 °F) Packaging and Weights Weight 0.454 kg | 1 lb Regulatory Compliance/Certifications Classification Agency CHINA-ROHS Above maximum concentration value ROHS Compliant **UK-ROHS** Compliant



Page 2 of 2

©2025 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: April 30, 2025

