



REGAL Faceplate only for RMT2122-RF-14 Tap

- \*Product complies with the Build America, Buy America Act (BABAA) requirements of the Infrastructure Investment and Jobs Act of 2021 (Pub. L. 117- 58, §§ 70901-70953), or is the subject of a waiver approved by the Secretary of Commerce or designee. Compliance requirements and waiver applicability vary based on government funding program. Check the laws and regulations for your specific program.

- Support DOCSIS® 3.1 expanded bandwidth up to1218 MHz
- Improve network performance with signal conditioning plug-ins
- High quality RF connection with auto-seize F-connectors
- Maintain existing Regal installed base with compatible faceplate upgrades
- Faceplate only options for cost effective upgrades to existing Regal deployments
- High level of network resilience with 6kV surge resistance on feederline and F-ports
- Maintain feederline RF and AC connections with faceplate removed with integrated bypass capability

Product Classification

|                         |   |
|-------------------------|---|
| Regional Availability   | Asia   Australia/New Zealand   EMEA   Latin America   North America |
| Product Type            | Faceplate for tap   |
| Product Series          | REGAL   |
| Government Requirements | Build America Buy America (BABA) compliant*                         |

General Specifications

|                           |   |
|---------------------------|---|
| Location of Manufacturing | Waived per BABA waiver for BEAD Program |
| Number of Ports           | 2                                       |

Dimensions

|        |                    |
|--------|--------------------|
| Height | 101.6 mm   4 in    |
| Depth  | 76.2 mm   3 in     |
| Length | 95.25 mm   3.75 in |

Electrical Specifications

|                                      |                       |
|--------------------------------------|-----------------------|
| Bandwidth                            | 5 – 1218 MHz MHz      |
| Insertion Loss, tap, nominal         | 14.5 dB               |
| Power Passing at 60/90V, maximum     | 12 A                  |
| Surge Protection, F port             | 6 kV Combination Wave |
| Surge Protection, input/output ports | 6 kV Combination Wave |

Environmental Specifications

**Operating Temperature**

-40 °C to +60 °C (-40 °F to +140 °F)

Packaging and Weights

**Weight**

0.454 kg | 1 lb

Regulatory Compliance/Certifications

| Agency     | Classification                    |
|------------|-----------------------------------|
| CHINA-ROHS | Above maximum concentration value |
| ROHS       | Compliant                         |
| UK-ROHS    | Compliant                         |

