596229-008-00 | SSP-PIQ/SP/U



STARLINE® Faceplate only for the SSP-PIQ/SP power inserter

- *Product complies with the Build America, Buy America Act (BABAA) requirements of the Infrastructure Investment and Jobs Act of 2021 (Pub. L. 117- 58, §§ 70901-70953), or is the subject of a waiver approved by the Secretary of Commerce or designee. Compliance requirements and waiver applicability vary based on government funding program. Check the laws and regulations for your specific program.
- Supports DOCSIS® 3.1 expanded bandwidth up to 1218 MHz
- Supports existing install base with backward compatible faceplates
- Superior flexibility in installation with rotatable faceplate and swivel center seizure mechanism
- Easily configured to enable or block AC power as needed in the network
- Protect valuable network equipment investment with optional heavy surge suppression in Power Inserter

Product Classification

Regional Availability

Asia | Australia/New Zealand | EMEA | Latin America | North America

Product Type Faceplate for power inserter

Product Series SSP-Q

Government FundingBuild America Buy America (BABA) compliant*

General Specifications

Location of Manufacturing Waived per BABA waiver for BEAD Program

Dimensions

 Height
 140.462 mm | 5.53 in

 Depth
 63.5 mm | 2.5 in

Length 140.462 mm | 5.53 in

Electrical Specifications

Current Handling, ac ports 20 A

Current Handling, RF ports 15 A

Operating Frequency Band 5 – 1218 MHz

Surge Protection Yes

Environmental Specifications



596229-008-00 | SSP-PIQ/SP/U

Operating Temperature

-40 °C to +60 °C (-40 °F to +140 °F)

Packaging and Weights

Weight 0.757 kg | 1.67 lb

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Above maximum concentration value

ROHS Compliant/Exempted UK-ROHS Compliant/Exempted

