# F4A-PDMDR-2M-X



FSJ4-50B SureFlex® Jumper with interface types 7-16 DIN Male and 7-16 DIN Male Right Angle, 2 m

### **Product Classification**

Product Type SureFlex® standard

Product Brand HELIAX® | SureFlex®

**Product Series** FSJ4-50B

General Specifications

Attachment, Connector B Field attachment

Body Style, Connector AStraightBody Style, Connector BRight angleInterface, Connector A7-16 DIN MaleInterface, Connector B7-16 DIN Male

Specification Sheet Revision Level A

**Dimensions** 

**Length** 2 m | 6.562 ft

Nominal Size 1/2 in

**Electrical Specifications** 

**DTF, Connector A** -32 dB

VSWR/Return Loss

Frequency Band VSWR, typical Return Loss, typical (dB)

**0–3000 MHz** 1.106 25.96 **2.2–2.7 GHz** 1.083 27.99

Jumper Assembly Sample Label





## **Environmental Specifications**

**Immersion Test Method** 

Meets IEC 60529:2001, IP68 in mated condition

## Regulatory Compliance/Certifications

**Agency** 

Classification

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system

#### Included Products

F4PDR-C

- 7-16 DIN Male Right Angle for 1/2 in FSJ4-50B

cable