1-port quasi-omni exposed dipole antenna, 450–470 MHz, 360° HPBW, fixed electrical tilt

- Broad response
- Moisture resistant
- Rugged, reliable design

General Specifications

| Antenna Type | Omni |
|----------------------------------|--|
| Band | Single band |
| Color | Silver |
| Grounding Type | RF connector inner conductor and body grounded to reflector and mounting bracket |
| Performance Note | Outdoor usage |
| Radiator Material | Aluminum |
| RF Connector Interface | N Male |
| RF Connector Location | End of flexible lead |
| RF Connector Quantity, high band | 0 |
| RF Connector Quantity, mid band | 0 |
| RF Connector Quantity, low band | 1 |
| RF Connector Quantity, total | 1 |
| Dimensions | |
| Length | 2,870.2 mm 113 in |
| Net Weight, without mounting kit | 11.3 kg 24.912 lb |
| | |

Electrical Specifications

| Impedance | 50 ohm |
|--------------------------|---------------|
| Operating Frequency Band | 450 - 470 MHz |
| Polarization | Vertical |

Electrical Specifications

| Frequency Band, MHz | 450-470 |
|---------------------|---------|
| Gain, dBi | 11.1 |

Page 1 of 3



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 12, 2025

DB411-B

| Beamwidth, Horizontal, degrees | 360 |
|---|------------|
| Beamwidth, Vertical, degrees | 14 |
| Beam Tilt, degrees | 0 |
| VSWR Return loss, dB | 1.5 14.0 |
| Input Power per Port, maximum, watts | 250 |

Mechanical Specifications

| Wind Loading @ Velocity, maximum | 266.9 N @ 100 mph (60.0 lbf @ 100 mph) |
|----------------------------------|--|
| Wind Speed, maximum | 161 km/h (100 mph) |

Regulatory Compliance/Certifications

| Agency | Classification |
|------------------------------|---|
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| Included Product db365-os | Pipe Mounting Kit that consists of two clamps for mounting antennas to round members 1.25 - 3.5 in (35 - 89 mm) OD round members. |
| * Footnotes | |
| Performance Note | Severe environmental conditions may degrade optimum performance |



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 12, 2025

Pipe Mounting Kit that consists of two clamps for mounting antennas to round members 1.25 - 3.5 in (35 - 89 mm) OD round members.

Product Classification

| Product Type | Pipe mounting kit |
|------------------------------|-------------------|
| General Specifications | |
| Application | Outdoor |
| Color | Silver |
| Dimensions | |
| Compatible Diameter, maximum | 88.9 mm 3.5 in |
| Compatible Diameter, minimum | 33 mm 1.299 in |
| Weight, net | 3.2 kg 7.055 lb |
| Material Specifications | |

Packaging and Weights

Material Type

| Included | Brackets Hardware |
|--------------------|---------------------|
| Packaging quantity | 2 |
| Weight, gross | 3.6 kg 7.937 lb |

Regulatory Compliance/Certifications

| Agency | Classification |
|---------------|--|
| CE | Compliant with the relevant CE product directives |
| CHINA-ROHS | Below maximum concentration value |
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| REACH-SVHC | Compliant as per SVHC revision on www.andrew.com/ProductCompliance |
| ROHS | Compliant |
| UK-ROHS | Compliant |
| | |

Galvanized steel



Page 3 of 3



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 12, 2025