### 1-port omni antenna, 450–482 MHz, 360° HPBW, fixed electrical tilt

- Omnidirectional antenna
- Rugged, durable design, heavy duty radome for minimum tip deflection
- Invert mountable

## General Specifications

Antenna Type Omni

Band Single band
Color Horizon blue

**Grounding Type** RF connector inner conductor and body grounded to reflector and mounting bracket

Performance Note Outdoor usage

Radome Material Fiberglass, UV resistant

Radiator MaterialBrassRF Connector InterfaceN FemaleRF Connector LocationBottom

RF Connector Quantity, high band 0
RF Connector Quantity, mid band 0
RF Connector Quantity, low band 1
RF Connector Quantity, total 1

#### Dimensions

**Length** 1435 mm | 56.496 in

Net Weight, without mounting kit  $3.6 \text{ kg} \mid 7.937 \text{ lb}$ 

Outer Diameter 50.8 mm | 2 in

## **Electrical Specifications**

**Impedance** 50 ohm

**Operating Frequency Band** 450 – 482 MHz

**Polarization** Vertical

## **Electrical Specifications**

Frequency Band, MHz 450-482



# DB633-C

Gain, dBi 5.1

Beamwidth, Horizontal, 360

degrees

**Beamwidth, Vertical, degrees** 35

Beam Tilt, degrees 0

VSWR | Return loss, dB 1.5 | 14.0 Input Power per Port, 500

maximum, watts

### Mechanical Specifications

**Wind Loading @ Velocity, maximum** 87.2 N @ 100 mph (19.6 lbf @ 100 mph)

Wind Speed, maximum 201 km/h (125 mph)

## Regulatory Compliance/Certifications

#### Agency Classification

CHINA-ROHS Below maximum concentration value

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

REACH-SVHC Compliant as per SVHC revision on www.andrew.com/ProductCompliance

ROHS Compliant UK-ROHS Compliant



#### Included Products

DB365-OS – Pipe Mounting Kit that consists of two clamps for mounting antennas to round members 1.25 - 3.5 in (35 - 89 mm) OD round members.

#### \* Footnotes

**Performance Note**Severe environmental conditions may degrade optimum performance



# DB365-0S

Pipe Mounting Kit that consists of two clamps for mounting antennas to round members 1.25 - 3.5 in (35 - 89 mm) OD round members.

### **Product Classification**

**Product Type** Pipe mounting kit

General Specifications

ApplicationOutdoorColorSilver

**Dimensions** 

Compatible Diameter, maximum88.9 mm | 3.5 inCompatible Diameter, minimum33 mm | 1.299 inWeight, net3.2 kg | 7.055 lb

Material Specifications

Material Type Galvanized steel

## Packaging and Weights

Included Brackets | Hardware

Packaging quantity 2

**Weight, gross** 3.6 kg | 7.937 lb

## Regulatory Compliance/Certifications

#### Agency Classification

CE Compliant with the relevant CE product directives

CHINA-ROHS Below maximum concentration value

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

REACH-SVHC Compliant as per SVHC revision on www.andrew.com/ProductCompliance

ROHS Compliant UK-ROHS Compliant



