VHLPX3-11W-6-QD/A



0.9m | 3 ft ValuLine® High Performance Low Profile Antenna, dualpolarized, 10.125–11.700 GHz, CPR90G flange, white antenna, composite broadband gray radome without flash, fully assembled/Quick Deploy pack—one-piece reflector

Product Classification

Product Type	
Product Brand	

Microwave antenna ValuLine®

General Specifications

Antenna Type	VHLPX - ValuLine® High Performance Low Profile Antenna, dual-polarized
Antenna Input	CPR90G
Antenna Color	White
Reflector Construction	One-piece reflector
Radome Color	Gray
Radome Material	Composite Broadband
Flash Included	No
Dimensions	
Diameter, nominal	0.9 m 3 ft

Electrical Specifications

Operating Frequency Band	10.125 - 11.700 GHz
Operating Frequency Band	10.125 - 11.700 GF

Packaging and Weights

Height, packed	1215 mm 47.835 in
Width, packed	698 mm 27.48 in
Length, packed	1162 mm 45.748 in
Packaging Type	Wooden crate
Volume	1 m³ 35.315 ft³
Weight, gross	58 kg 127.868 lb
Weight, net	17 kg 37.479 lb

Page 1 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 12, 2025

VHLPX3-11W-6-QD/A

Regulatory Compliance/Certifications

Agency Classification

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

* Footnotes

Operating Frequency Band Bands correspond with CCIR recommendations or common allocations used throughout the world. Other ranges can be accommodated on special order.

Packaging TypeAndrew standard packing is suitable for export. Antennas are shipped as standard in totally
recyclable cardboard or wire-bound crates (dependent on product). For your convenience, Andrew
offers heavy duty export packing options.

Page 2 of 2

