36000001 | 10/8MB DUCT EMPTY

ConQuest® Empty Conduit, 10 mm OD, 8 mm ID, black

• *Product complies with the Build America, Buy America Act (BABAA) requirements of the Infrastructure Investment and Jobs Act of 2021 (Pub. L. 117- 58, §§ 70901-70953), or is the subject of a waiver approved by the Secretary of Commerce or designee. Compliance requirements and waiver applicability vary based on government funding program. Check the laws and regulations for your specific program.

Product Classification

Hydrostatic Design Basis

Regional Availability	North America	
Product Type	Empty conduit	
Product Brand	ConQuest®	
Government Requirements	Build America Buy America (BABA) compliant*	
General Specifications		
Color	Black	
Conduit Type	Non-toneable	
Density Test Method	ASTM D792A	
Density, maximum	0.955 g/cm³ 0.035 lb/in³	
Density, minimum	0.941 g/cm³ 0.034 lb/in³	
Design Standard	ASTM D3350-05	
Location of Manufacturing	Catawba, North Carolina	
Wall Type	Smooth	
Dimensions		
Inner Diameter, nominal	7.976 mm 0.314 in	
Outer Diameter, nominal	10.008 mm 0.394 in	
Wall Thickness, minimum	0.838 mm 0.033 in	
Nominal Size	10 mm	
Material Specifications		
Flexural Modulus, minimum	551.581 N/mm² 80000 psi	
Flexural Property Test Method	ASTM D790	

Page 1 of 2

©2024 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: October 1, 2024

Not pressure rated



36000001 | 10/8MB DUCT EMPTY

D2837
ensity polyethylene (HDPE)
D1238
'10 min

Mechanical Specifications

Minimum Bend Radius, unsupported	101.6 mm 4 in
Tensile Property Test Method	ASTM D638
Tensile Strength at yield, minimum	20.684 N/mm² 3000 psi
Pulling Tension, maximum	54.431 kg 120 lb

Environmental Specifications

Environmental Stress Crack Resistance	Failure rate of 10% within 96 hours
Environmental Stress Test Method	ASTM D1693, ESCR Condition B

Packaging and Weights

Weight, net

28.275 kg/km | 19 lb/kft

Regulatory Compliance/Certifications

 Agency
 Classification

 ISO 9001:2015
 Designed, manufactured and/or distributed under this quality management system

* Footnotes

Environmental Stress Crack Resistance ESCR-Environmental Stress Crack Resistence

©2024 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: October 1, 2024

