PB-G3T-4



Tapered Pipe Frame Stand-Off Bracket, 36 in, for 4 in to 8 in OD legs

| Product Classification | |
|----------------------------|--|
| Product Type | Stand-off mount |
| Ordering Note | ANDREW® standard product in the United States and Canada |
| General Specifications | |
| Mounting | Legs, 101.6–203.2 mm (4–8 in) OD |
| Tower Taper | Tapered |
| Dimensions | |
| Height | 1,447.8 mm 57 in |
| Width | 254 mm 10 in |
| Length | 838.2 mm 33 in |
| Mounting Diameter, maximum | 203.2 mm 8 in |
| Mounting Diameter, minimum | 101.6 mm 4 in |
| Stand-off Distance | 914.4 mm 36 in |
| Material Specifications | |
| Material Type | Hot dip galvanized steel |
| Mechanical Specifications | |
| Wind Rating | 120 mph (BWS) at 150 ft AGL 140 mph (3-second gust) at 150 ft AGL using Exposure D per FBC |
| Wind Rating Test Method | TIA/EIA-222 |
| | |
| Packaging and Weights | |

IncludedClampsStand-offPackaging quantity1Weight, net62.6 kg | 138.009 lb

Page 1 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 12, 2025

PB-G3T-4

Regulatory Compliance/Certifications

Agency Classification

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

* Footnotes

Wind Rating BWS-Base Wind Speed; FBC-Florida Building Code



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 12, 2025