


# PG-RM06



PIM-Guard® Round Member Cable Support Bracket 6 ports for stackable hangers (up to 3 per port). Install with torque wrench set at 5 to 7 ft-lb to meet carrier PIM requirements. For patents, see [www.cs-pat.com](http://www.cs-pat.com)

## Product Classification

<b>Portfolio</b>	CommScope®
<b>Product Type</b>	Antenna/RRU Cable Support
<b>Product Brand</b>	PIM-Guard®
<b>Ordering Note</b>	CommScope® standard product (Global)
<b>Warranty</b>	One year

## General Specifications

<b>Cable Runs, quantity</b>	6
<b>Hole, quantity</b>	6
<b>Mounting</b>	Pipe, 60.3–88.9 mm (2-3/8 in to 3-1/2 in) OD

## Dimensions

<b>Height</b>	50.8 mm   2 in
<b>Width</b>	50.8 mm   2 in
<b>Length</b>	198.12 mm   7.8 in
<b>Mounting Diameter, maximum</b>	60.96 mm   2.4 in
<b>Mounting Diameter, minimum</b>	88.9 mm   3.5 in
<b>Hole Size</b>	3/4 in

## Material Specifications

<b>Material Type</b>	Hot dip galvanized steel
----------------------	--------------------------

## Packaging and Weights

<b>Packaging quantity</b>	1
<b>Weight, net</b>	2.3 kg   5.071 lb

## Regulatory Compliance/Certifications

# PG-RM06

---

## Agency

CHINA-ROHS

ISO 9001:2015

REACH-SVHC

ROHS

UK-ROHS



## Classification

Below maximum concentration value

Designed, manufactured and/or distributed under this quality management system

Compliant as per SVHC revision on [www.commscope.com/ProductCompliance](http://www.commscope.com/ProductCompliance)

Compliant

Compliant

## \* Footnotes

### Warranty

For more information, please consult our Product Warranty guidelines