

CK0622N001 | OC-ADK-S5-S5-NNCS-N

Fiber Optic Simplex Adapter, Multimode SC/UPC, aqua, with FIST retainer

- High quality zirconia ceramic split sleeves ensuring high precision alignment, reliability and improved reconnect ability
- Translucent easy grip dust cap and integrated mounting clips
- High quality one piece housing, no ultrasonic welding

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Product Type	Fiber adapter
Product Series	OC-ADK

General Specifications

Body Style	Simplex
Color	Aqua
Interface	SC/UPC
Mounting	Square flange
Total Ports, quantity	1
Transmission Standards	IEC 60754-1 IEC 61300-3-42

Material Specifications

Alignment Sleeve Material	Ceramic
---------------------------	---------

Mechanical Specifications

Coupling Retention Force	70 N 15.737 lbf
--------------------------	-------------------

Optical Specifications

Fiber Mode	Multimode
Insertion Loss, maximum	0.1 dB

Environmental Specifications

Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
-----------------------	--------------------------------------

Packaging and Weights

Packaging quantity	1
--------------------	---

CK0622N001 | OC-ADK-S5-S5-NNCS-N

Packaging Type Bag