# DPJ08-208-27F



HELIAX® Remote Radio Head Power Y-Cable, OVP Top Enclosure End: one Red and one Black 8 AWG Conductors. RRU end: 2x8 AWG power cords with 1 Red and 1 Black conductors per cord. RRU length 2 feet, OVP length 25 feet

#### **Product Classification**

Regional AvailabilityNorth AmericaPortfolioCommScope®

**Product Type** Power cable assembly

Product Series PWRT

Ordering Note CommScope® non-standard product

### General Specifications

**Cable Type** Power

Construction Type Discrete power cable | Non-armored

Jacket ColorBlackSupported ApplicationIndustrial

**Dimensions** 


Cable Length 8.23 m | 27 ft

**Diameter Over Jacket, nominal** 11.303 mm | 0.445 in

Outer Shield (Braid) Gauge 36 AWG

### Cross Section Drawing





#### Main Cable



Page 1 of 2

# DPJ08-208-27F

### Material Specifications

Conductor Material Tinned copper

**Dielectric Material** PVC

Drain Wire MaterialTinned copperFiller MaterialPolypropyleneGround Wire MaterialTinned copper

Insulation Material, singlesPVCJacket MaterialPVCOuter Shield (Braid) Coverage65 %

Outer Shield (Braid) Material Tinned copper

Outer Shield (Tape) Material Aluminum/Poly, non-bonded

## **Environmental Specifications**

**Operating Temperature**  $-40 \,^{\circ}\text{C} \text{ to } +90 \,^{\circ}\text{C} \, (-40 \,^{\circ}\text{F to } +194 \,^{\circ}\text{F})$ 

**Environmental Space** UV resistant for outdoor and/or direct burial installations

Safety Standard NEC Article 336 (Type TC)

Packaging and Weights

**Cable weight** 312.514 kg/km | 210 lb/kft

## Regulatory Compliance/Certifications

#### Agency Classification

CHINA-ROHS Below maximum concentration value

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant UK-ROHS Compliant



#### \* Footnotes

**Operating Temperature** Specification applicable to non-terminated bulk fiber cable

