


MC-PK8-C



Low-Profile Co-location Platform Kit, 8 ft face, 12 in to 38 in OD, (9) 2-3 /8" OD x 72" Pipes, with Support Rail Kit

Please contact ANDREW for detailed drawings prior to ordering.

Product Classification

| | |
|----------------------|-----------------------|
| Product Type | Monopole platform kit |
| Ordering Note | NSTD445 Compliant |

General Specifications

| | |
|--------------------------|------------------------------------|
| Mounting | Monopole, 305–965 mm (12–38 in) OD |
| Pipe, quantity | 9 |
| Sectors, quantity | 3 |

Dimensions

| | |
|-----------------------------------|----------------------|
| Height | 1,828.8 mm 72 in |
| Face Width | 2.438 m 8 ft |
| Width | 2,438.4 mm 96 in |
| Pipe Length | 1,828.8 mm 72 in |
| Face Support Pipe Diameter | 88.9 mm 3.5 in |
| Mounting Diameter, maximum | 965.2 mm 38 in |
| Mounting Diameter, minimum | 304.8 mm 12 in |
| Pipe Outer Diameter | 60.325 mm 2.375 in |
| Stand-off Distance | 914.4 mm 36 in |

Material Specifications

| | |
|----------------------|--------------------------|
| Material Type | Hot dip galvanized steel |
|----------------------|--------------------------|

Mechanical Specifications

| | |
|--------------------------------|---|
| Wind Rating | For Specifications, please contact your local ANDREW representative |
| Wind Rating Test Method | TIA/EIA-222 |

MC-PK8-C

Packaging and Weights

| | |
|---------------------------|---|
| Included | Hardware Plain end pipes (9) Platform Rail Ring mount |
| Packaging quantity | 1 |
| Weight, net | 622.782 kg 1373 lb |

Regulatory Compliance/Certifications

| Agency | Classification |
|---------------|-----------------------------------|
| CHINA-ROHS | Above maximum concentration value |
| ROHS | Compliant/Exempted |
| UK-ROHS | Compliant/Exempted |



* Footnotes

| | |
|--------------------|--|
| Wind Rating | BWS—Base Wind Speed; FBC—Florida Building Code |
|--------------------|--|