

Fiber Optic Patch Cord, Multi-fiber, Singlemode, SC/UPC to LC/UPC, Yellow

Product Classification

Regional Availability

Asia | Australia/New Zealand | Europe | Latin America | Middle East

/Africa | North America

Product Type Fiber distribution cable assembly

Product Series MA

Ordering Note 2.0mm cable is only available as Plenum | 2.0mm subunit only available in 4, 8 and

12 fibers | Pulling sock not available on fiber counts 4, 8 or 12

General Specifications


Color, boot A Blue
Color, connector A Blue
Color, boot B Blue
Color, connector B Blue
Interface, Connector A SC/UPC
Interface, Connector B LC/UPC

Jacket Color Yellow

Dimensions

Diameter Over Jacket 1.2 mm | 0.047 in


Ordering Tree




MA-SE

Representative Image


4, 8 and 12 Fiber Assembly Image



24 – 144 Fiber Assembly Image



MPO Connectors on Side B (Optional)



Optical Specifications

Fiber Mode	Singlemode
Fiber Type	OS2
Insertion Loss, maximum, connector A	0.18 dB
Insertion Loss, maximum, connector B	0.18 dB
Return Loss, minimum, connector A	52 dB
Return Loss, minimum, connector B	52 dB

Environmental Specifications

Environmental Space Plenum

Page 3 of 4

MA-SE

Qualification Standards GR-326 CORE | GR-449-CORE

Packaging and Weights

Packaging quantity 1

