

Fiber Optic Patch Cord, Multi-fiber, Singlemode, SC/APC to LC/APC, Yellow

Product Classification

Regional Availability

Asia | Australia/New Zealand | Europe | Latin America | Middle East

/Africa | North America

Product Type Fiber distribution cable assembly

Product Series MA

Ordering Note 2.0mm cable is only available as Plenum | 2.0mm subunit only available in 4, 8 and

12 fibers | Pulling sock not available on fiber counts 4, 8 or 12

General Specifications


Color, boot A Green
Color, connector A Green
Color, boot B Green
Color, connector B Green
Interface, Connector A SC/APC
Interface, Connector B LC/APC
Jacket Color Yellow

Dimensions

Diameter Over Jacket 1.2 mm | 0.047 in

MA-SF


Ordering Tree




MA-SF

Representative Image


4, 8 and 12 Fiber Assembly Image



24 – 144 Fiber Assembly Image



MPO Connectors on Side B (Optional)



Optical Specifications

Fiber Mode	Singlemode
Fiber Type	OS2
Insertion Loss, maximum, connector A	0.3 dB
Insertion Loss, maximum, connector B	0.3 dB
Return Loss, minimum, connector A	65 dB
Return Loss, minimum, connector B	65 dB

Environmental Specifications

Environmental Space Plenum

Page 3 of 4

MA-SF

Qualification Standards GR-326 CORE | GR-449-CORE

Packaging and Weights

Packaging quantity 1

