

MA-SN



Fiber Optic Patch Cord, Multi-fiber, Singlemode, SC/UPC to LC/APC, Yellow

Product Classification

| | |
|-----------------------|--|
| Regional Availability | Asia Australia/New Zealand Europe Latin America Middle East /Africa North America |
| Product Type | Fiber distribution cable assembly |
| Product Series | MA |
| Ordering Note | 2.0mm cable is only available as Plenum 2.0mm subunit only available in 4, 8 and 12 fibers Pulling sock not available on fiber counts 4, 8 or 12 |

General Specifications

| | |
|------------------------|--------|
| Color, boot A | Blue |
| Color, connector A | Blue |
| Color, boot B | Green |
| Color, connector B | Green |
| Interface, Connector A | SC/UPC |
| Interface, Connector B | LC/APC |
| Jacket Color | Yellow |

Dimensions


| | |
|----------------------|-------------------|
| Diameter Over Jacket | 1.2 mm 0.047 in |
|----------------------|-------------------|

Ordering Tree




Representative Image


4, 8 and 12 Fiber Assembly Image



24 – 144 Fiber Assembly Image



MPO Connectors on Side B (Optional)



Optical Specifications

| | |
|--------------------------------------|------------|
| Fiber Mode | Singlemode |
| Fiber Type | OS2 |
| Insertion Loss, maximum, connector A | 0.18 dB |
| Insertion Loss, maximum, connector B | 0.3 dB |
| Return Loss, minimum, connector A | 52 dB |
| Return Loss, minimum, connector B | 65 dB |

Environmental Specifications

| | |
|---------------------|--------|
| Environmental Space | Plenum |
|---------------------|--------|

MA-SN

| | |
|-------------------------|------------------------------------|
| Qualification Standards | GR-326 CORE GR-409 GR-449-CORE |
| Packaging and Weights | |
| Packaging quantity | 1 |