

# KVVSS-65A-3XKIT



Tri-sector solution that includes 3 KVVSS-65A-R3-V1 antennas and mounting kit to install them on a pipe

- Suitable for attachment to 3.5-6.5 in or 89-165 mm outer diameter pipe
- Compatible with canister concealment shrouds with inner diameter > 23.5 in (597mm)
- Minimum shroud diameter is the same for all applicable pipe diameters

This product will be discontinued on: December 31, 2025

## General Specifications

Band	Multiband
Performance Note	Outdoor usage
RF Connector Interface	4.3-10 Female
RF Connector Location	Bottom
RF Connector Quantity, high band	12
RF Connector Quantity, mid band	12
RF Connector Quantity, low band	6
RF Connector Quantity, total	30

## Dimensions

Net Weight, with mounting kit	107 kg   235.894 lb
-------------------------------	---------------------

## Electrical Specifications

Operating Frequency Band	1695 – 2690 MHz   3100 – 4200 MHz   617 – 960 MHz
--------------------------	---

## Packaging and Weights

Width, packed	601 mm   23.661 in
Depth, packed	1027 mm   40.433 in
Length, packed	1667 mm   65.63 in
Weight, gross	135.5 kg   298.726 lb

## Regulatory Compliance/Certifications

# KVVSS-65A-3XKIT

---

Agency	Classification
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on <a href="http://www.andrew.com/ProductCompliance">www.andrew.com/ProductCompliance</a>
ROHS	Compliant
UK-ROHS	Compliant



\* Footnotes

Performance Note	Severe environmental conditions may degrade optimum performance
------------------	---