760254772 | C-008-CN-5K-M08BK/28D/GY/D



Indoor/Outdoor Low Smoke Zero Halogen, LazrSPEED® Central Loose Tube Fiber Optic Cable, 8-fiber, Multimode OM4, Gel-free, black. Provides Rodent Resistance.

Product Classification

Regional Availability

Asia | Australia/New Zealand | EMEA

Portfolio CommScope®

Product Type Fiber indoor/outdoor cable

Product Series C-CN

General Specifications

Cable TypeLoose tubeSubunit TypeGel-free

Filler, quantity 1

Jacket ColorBlackJacket MarkingMetersJacket Marking MethodInkjet

Jacket Marking TextCOMMSCOPE GB OPTICAL CABLE 760254772 INT/EXT RODENT RESIST

DLT 8X50/125 OM4 EN50575 CLASS D (Serial number) (metre mark)

Fibers per Subunit, quantity 8

Total Fiber Count 8

Dimensions


 Cable Length
 2000 m | 6,561.68 ft

 Diameter Over Jacket
 6.4 mm | 0.252 in

Representative Image



760254772 | C-008-CN-5K-M08BK/28D/GY/D



Mechanical Specifications

Minimum Bend Radius, loaded139.7 mm | 5.5 inMinimum Bend Radius, unloaded129.5 mm | 5.098 inTensile Load, long term, maximum650 N | 146.126 lbfTensile Load, short term, maximum1250 N | 281.011 lbf

Optical Specifications

Fiber Type OM4

Optical Specifications, Wavelength Specific

Attenuation, maximum 1.00 dB/km @ 1,300 nm | 3.50 dB/km @ 850 nm

Standards Compliance IEC 60794-1 | TIA-492AAAD (OM4)

Environmental Specifications

Installation temperature $-5 \,^{\circ}\text{C}$ to $+50 \,^{\circ}\text{C}$ (+23 $^{\circ}\text{F}$ to +122 $^{\circ}\text{F}$)

Operating Temperature $-20 \,^{\circ}\text{C}$ to $+70 \,^{\circ}\text{C}$ (-4 $^{\circ}\text{F}$ to +158 $^{\circ}\text{F}$)

Storage Temperature $-10 \,^{\circ}\text{C}$ to $+70 \,^{\circ}\text{C}$ (+14 $^{\circ}\text{F}$ to +158 $^{\circ}\text{F}$)

EN50575 CPR Cable EuroClass Fire PerformanceDcaEN50575 CPR Cable EuroClass Smoke Ratings2EN50575 CPR Cable EuroClass Droplets Ratingd2EN50575 CPR Cable EuroClass Acidity Ratinga1

Page 2 of 3



760254772 | C-008-CN-5K-M08BK/28D/GY/D

Environmental Space

Low Smoke Zero Halogen (LSZH)

Packaging and Weights

Cable weight 47 kg/km | 31.583 lb/kft

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Below maximum concentration value

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant UK-ROHS Compliant



Included Products

CS-5K-LT – LazrSPEED® 550 OM4 Bend-Insensitive Multimode

Fiber

* Footnotes

Operating Temperature Specification applicable to non-terminated bulk fiber cable

