860660825



LC UniBoot 1.5 mm Multimode Aqua LC UNIBOOT duplex connector

Product Classification

Regional Availability

Asia | Australia/New Zealand | EMEA | Latin America | North America

Fiber connector

Portfolio CommScope®

Product Brand LazrSPEED® | SYSTIMAX ULL

Product Series Uniboot

General Specifications

Body StyleDuplexColorBeigeInterfaceLC/UPCInterface FeatureUniboot

Dimensions

Product Type

Compatible Cable Diameter 1.5 mm | 0.059 in

Material Specifications

Ferrule Material Zirconia

Mechanical Specifications

Cable Retention Strength, maximum $11.24 \text{ lb} @ 0 \degree + 4.40 \text{ lb} @ 90 \degree$

Optical Specifications

Fiber Mode Multimode

Insertion Loss Change, mating 0.3 dB

Optical Components Standard ANSI/TIA-568-C.3

Insertion Loss, maximum0.1 dBInsertion Loss, ULL, maximum0.15 dB



860660825

Insertion Loss, ULL, typical0.13 dBReturn Loss, minimum35 dB

Packaging and Weights

Packaging quantity

* Footnotes

Insertion Loss Change, mating TIA-568: Maximum insertion loss change after 500 matings

