

ATSBT-BOTTOM-FF-5G | D85E01P87



Bottom Smart Bias Tee, 600-4200 MHz, 4.3-10

- Injects AISG power and control signals onto a coaxial cable line
- Reduces cable and site lease costs by eliminating the need for AISG home run cables
- AISG 1.1 and 2.0 compliant
- Operates at 10-30 Vdc
- Weatherproof AISG connectors
- Intuitive schematics simplify and ensure proper installation
- Enhanced lightning protection plus grounding stud for additional surge protection
- 4.3-10 female connector (ANT)
- 4.3-10 female connector (BTS)

Product Classification

Product Type RET bias tee

General Specifications

AISG Input Connector	8-pin DIN Male
Antenna Interface	4.3-10 Female
Antenna Interface Signal	AISG data RF dc
BTS Interface	4.3-10 Female
BTS Interface Signal	RF dc Blocked
Color	Silver
EU Certification	CE
Grounding Lug Thread Size	M6
Smart Bias Tee Type	10~30 V Bottom

Dimensions

Height	68 mm 2.677 in
Width	98 mm 3.858 in
Depth	60 mm 2.362 in

Electrical Specifications

3rd Order IMD	-161 dBc
3rd Order IMD Test Method	Two +43 dBm CW Tones
Insertion Loss, typical	0.1 dB

ATSBT-BOTTOM-FF-5G | D85E01P87

Electromagnetic Compatibility (EMC)	CFR 47 Part 15, Subpart B, Class B EN 55022, Class B ICES-003 Issue 4 CAN /CSA-CEI/IEC CISPR 22:02
Impedance	50 ohm
Interface Protocol Signal	Data dc
Lightning Surge Capability	5 times @ -3 kA 5 times @ 3 kA
Lightning Surge Capability Test Method	IEC 61000-4-5, Level X
Lightning Surge Capability Waveform	1.2/50 voltage and 8/20 current combination waveform
Operating Frequency Band	600 – 4200 MHz
Power Consumption, maximum	0.6 W
Protocol	AISG 1.1 AISG 2.0
RF Power, maximum	500 W (CW Tone)
Voltage Range	10–30 Vdc
VSWR Return Loss	1.09:1 27 dB, typical

Material Specifications

Material Type	Aluminum
---------------	----------

Environmental Specifications

Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Ingress Protection Test Method	IEC 60529:2001, IP67

Packaging and Weights

Weight, net	0.9 kg 1.984 lb
-------------	-------------------

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Above maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant/Exempted
UK-ROHS	Compliant/Exempted

