

LS2-HMHM-2M-PB



LSF2-50 SureFlex® Jumper with interface types 4.3-10 Male and 4.3-10 Male, with Integrated Birdproofing Shell 2m

- WARNING: DO NOT MATE WITH 4.1-9.5 DIN

Product Classification

Product Type	SureFlex® Premium, static PIM
Product Brand	HELIAX® SureFlex®
Product Series	LSF2-50

General Specifications

Body Style, Connector A	Straight
Body Style, Connector B	Straight
Interface, Connector A	4.3-10 Male
Interface, Connector B	4.3-10 Male
Specification Sheet Revision Level	A

Dimensions

Length	2 m 6.562 ft
Nominal Size	3/8 in

Electrical Specifications

3rd Order IMD	-119 dBm
3rd Order IMD Test Method	Two +43 dBm carriers

VSWR/Return Loss

Frequency Band	VSWR	Return Loss (dB)
698–970 MHz	1.065	30
1700–2200 MHz	1.065	30
2200–2700 MHz	1.083	28
3400–3800 MHz	1.222	20
3800–6000 MHz	1.222	20

Jumper Assembly Sample Label

LS2-HM2M-2M-PB



Environmental Specifications

Immersion Test Method Meets IEC 60529:2001, IP68 in mated condition