


# SFG21HD-12-B



G21HD High Capacity Sector Frame, 12.5 ft x 2.88 in OD face pipes, Base Kit Only. No antenna pipes.

## Product Classification

Product Type	High capacity Tower sector frame
Product Series	G2

## General Specifications

Application	4G LTE antenna/radio mount
Mounting	Angle 60°, 203.2 mm (8 in)   Straight or tapered legs up to 203.2 mm (8 in) OD
Patent Number	Patent pending
Pipe, quantity	0
Sectors, quantity	1
Tower Taper	Non-tapered   Tapered

## Dimensions

Face Width	3.81 m   12.5 ft
Width	3,810 mm   150 in
Face Support Pipe Diameter	73.025 mm   2.875 in
Mounting Diameter, maximum	218.44 mm   8.6 in
Mounting Diameter, minimum	38.1 mm   1.5 in
Stand-off Distance	889 mm   35 in

## Material Specifications

Material Type	Hot dip galvanized steel
---------------	--------------------------

## Mechanical Specifications

Wind Rating	For Specifications, please contact your local ANDREW representative
Wind Rating Test Method	TIA/EIA-222-G

## Packaging and Weights

# SFG21HD-12-B

---

Included	Frame   Stiff arm   Tower attachment
Packaging quantity	1

## Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Above maximum concentration value
ROHS	Compliant/Exempted
UK-ROHS	Compliant/Exempted



## \* Footnotes

Wind Rating	BWS—Base Wind Speed; FBC—Florida Building Code
-------------	--