SFG23HDX-12-B



G23HDX High Capacity Sector Frame, 12.5 ft x 2.88 in OD face pipes, Base Kit Only. No antenna pipes.

Product Classification

Product Type High capacity Tower sector frame

Product Series G2

General Specifications

Mounting Angle 60°, 203.2 mm (8 in) | Straight or tapered legs up to 203.2 mm (8 in) OD

Patent Number Patent pending

Pipe, quantity 0
Sectors, quantity 1

Tower Taper Non-tapered | Tapered

Dimensions

Face Width 3.81 m | 12.5 ft

Width 3,810 mm | 150 in

Face Support Pipe Diameter 73.025 mm | 2.875 in

Mounting Diameter, maximum 218.44 mm | 8.6 in

Stand-off Distance 1,066.8 mm | 42 in

Material Specifications

Mounting Diameter, minimum

Material Type Hot dip galvanized steel

Mechanical Specifications

Wind Rating For Specifications, please contact your local ANDREW representative

38.1 mm | 1.5 in

Wind Rating Test Method TIA/EIA-222-G

Packaging and Weights

Included Frame | Stiff arms (2) | Tower attachment

ANDREW® an Amphenol company

SFG23HDX-12-B

Packaging quantity

1

* Footnotes

Wind Rating

BWS-Base Wind Speed; FBC-Florida Building Code

