## PML-SU2-72



Large Leg Universal Sliding Pipe Mount Kit, 2-3/8 in OD x 72 in pipe

Product Classification	
Product Type	Pipe mount
General Specifications	
Mounting	Angle 60°, 406.4 mm (16 in)   Angle 90°, 304.8 mm (12 in)   Straight or tapered legs up to 406.4 mm (16 in) OD
Note	One 96 in x 8 in panel antenna per sector
Pipe, quantity	1
Tower Taper	Non-tapered   Tapered
Dimensions	
Height	1,828.8 mm   72 in
Width	304.8 mm   12 in
Length	304.8 mm   12 in
Pipe Length	1,828.8 mm   72 in
Mounting Diameter, maximum	406.4 mm   16 in
Mounting Diameter, minimum	0 mm   0 in
Pipe Outer Diameter	60.96 mm   2.4 in
Stand-off Distance	203.2 mm   8 in
Material Specifications	
Material Type	Hot dip galvanized steel
Mechanical Specifications	
Wind Rating	120 mph (BWS) at 150 ft AGL
Wind Rating Test Method	TIA/EIA-222
Dackaging and Migights	

## Packaging and Weights

Page 1 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 12, 2025

## PML-SU2-72

Included	Pipe   Sliding pipe mount brackets   Universal saddle mount
Packaging quantity	1
Weight, net	45.8 kg   100.972 lb
Regulatory Compliance/Certifications	
Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
* Footnotes	

Wind Rating BWS-Base Wind Speed; FBC-Florida Building Code

Page 2 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 12, 2025