## PMI -SU4-63



## Large Leg Universal Sliding Pipe Mount Kit, 4-1/2 in OD x 63 in pipe

## **Product Classification**

Product Type Pipe mount

General Specifications

**Mounting** Angle 60°, 406.4 mm (16 in) | Angle 90°, 304.8 mm (12 in) | Straight or tapered legs up to 406.4

mm (16 in) OD

**Note** One 8 ft microwave antenna with stiff arm

Pipe, quantity 1

Tower Taper Non-tapered | Tapered

**Dimensions** 

 Height
 1,600.2 mm | 63 in

 Width
 304.8 mm | 12 in

 Length
 304.8 mm | 12 in

**Pipe Length** 1,600.2 mm | 63 in

Mounting Diameter, maximum 406.4 mm | 16 in

Pipe Outer Diameter114.3 mm | 4.5 inStand-off Distance203.2 mm | 8 in

Material Specifications

Material Type Hot dip galvanized steel

Mechanical Specifications

Wind Rating 120 mph (BWS) at 150 ft AGL

Wind Rating Test Method TIA/EIA-222

Packaging and Weights



## PML-SU4-63

Included Pipe | Sliding pipe mount brackets | Universal saddle mount

Packaging quantity 1

**Weight, net** 62.6 kg | 138.009 lb

Regulatory Compliance/Certifications

Agency Classification

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

\* Footnotes

Wind Rating BWS—Base Wind Speed; FBC—Florida Building Code

