## SF-DPM2-72



### Co-location Dual Pipe Mount Kit; includes (2) 2-3/8 in OD x 72 in pipes

#### **Product Classification**

**Product Type** Co-location dual pipe mount kit

General Specifications

**Mounting** Angle 60°, 203.2 mm (8 in) | Angle 90°, 152.4 mm (6 in) | Straight or tapered legs up to 203.2

mm (8 in) OD

**Note** Two 72 in x 8 in panel antenna per sector

Pipe, quantity 2

Tower Taper Non-tapered | Tapered

**Dimensions** 

**Height** 1,828.8 mm | 72 in

**Face Width** 1.463 m | 4.8 ft

**Width** 1,447.8 mm | 57 in

**Length** 0.396 m | 1.3 ft

**Pipe Length** 1,828.8 mm | 72 in

Face Support Pipe Diameter 88.9 mm | 3.5 in

Mounting Diameter, maximum 203.2 mm | 8 in

Mounting Diameter, minimum 0 mm | 0 in

Pipe Outer Diameter 60.96 mm | 2.4 in

**Stand-off Distance** 391.16 mm | 15.4 in

Material Specifications

Material Type Hot dip galvanized steel

Mechanical Specifications

Wind Rating 120 mph (BWS) at 150 ft AGL | 140 mph (3-second gust) at 150 ft AGL using Exposure D per FBC

Wind Rating Test Method TIA/EIA-222



# SF-DPM2-72

### Packaging and Weights

Included Clamps | Frame | Pipe mounts | Pipes | Saddle mounts

Packaging quantity 1

**Weight, net** 115.5 kg | 254.634 lb

### Regulatory Compliance/Certifications

Agency Classification

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

\* Footnotes

Wind Rating BWS—Base Wind Speed; FBC—Florida Building Code

