## TF-ML2S2-8



Tower Face Mount with dual 8 ft  $\times$  2-3/8 in OD face pipe supports, includes pipe

## **Product Classification**

**Product Type** Tower face mount

General Specifications

Mounting Angle 60°, 203.2 mm (8 in) | Angle 90°, 152.4 mm (6 in) | Straight or tapered legs up to 203.2

mm (8 in) OD

Pipe, quantity

Tower Taper Non-tapered | Tapered

**Dimensions** 

**Height** 1,600.2 mm | 63 in

**Face Width** 2.438 m | 8 ft

**Width** 2,438.4 mm | 96 in

**Length** 304.8 mm | 12 in

**Pipe Length** 1,600.2 mm | 63 in

Face Support Pipe Diameter 60.96 mm | 2.4 in

Mounting Diameter, maximum 203.2 mm | 8 in

**Mounting Diameter, minimum** 0 mm | 0 in

Pipe Outer Diameter 114.3 mm | 4.5 in

Material Specifications

Material Type Hot dip galvanized steel

Mechanical Specifications

Wind Rating 120 mph (BWS) at 100 ft AGL

Wind Rating Test Method TIA/EIA-222

## Packaging and Weights



## TF-ML2S2-8

Included Crossover plates | Pipes | Saddle mounts

Packaging quantity 1

**Weight, net** 238.181 kg | 525.1 lb

\* Footnotes

Wind Rating BWS—Base Wind Speed; FBC—Florida Building Code

