

HFDC-24FIBER



HELIAX® Fiber Distribution Closure 24 fibers - 12 DLCs UPC.

Product Classification

Regional Availability

China | EMEA | Europe | India | Latin America | Middle East/Africa | North America

Product Type

Fiber distribution closure

Product Brand

HELIAX®

General Specifications

Application

Used as a fiber junction box

Total Fiber Adapters

12

Color

Black

Doors, quantity

2

Mounting

Pipe, 44–114 mm (1.75–4.5 in) OD | Wall

Total Fibers, quantity

24

Total Ports, quantity

12

Dimensions

Height

370 mm | 14.567 in

Width

214 mm | 8.425 in

Depth

118 mm | 4.646 in

Jumper Breakout Length, Maximum

85 mm | 3.346 in

Jumper Outlet, Quantity, Maximum

12

Jumper Outlet Diameter, Minimum

0 mm | 0 in

Jumper Outlet Diameter, Maximum

7 mm | 0.276 in

Trunk Entry, Diameter, Minimum

5.5 mm | 0.217 in

Trunk Entry, Diameter, Maximum

17.5 mm | 0.689 in

Trunk Entry, Quantity, Maximum

4

Material Specifications

HFDC-24FIBER

Material Type High-impact polycarbonate, UV resistant

Mechanical Specifications

Impact Test Method EN62262 | IEC62262: IK07

Environmental Specifications

Operating Temperature -40 °C to +75 °C (-40 °F to +167 °F)

Qualification Standards IEC 60529, IP68

Packaging and Weights

Included Mounting kit

Weight, net 2.65 kg | 5.842 lb