


# RT-DF15-4-120



PIM-Guard High Capacity DUAL Non-Penetrating Roof Frame with Optimized Antenna Spacing 15 ft face, four 2-7/8 in OD x 120 in pipes

## Product Classification

Product Type	Non-penetrating roof frame
Product Brand	PIM-guard

## General Specifications

Mounting	Non-penetrating
Pipe, quantity	4

## Dimensions

Height	3,048 mm   120 in
Face Width	4.572 m   15 ft
Width	4,572 mm   180 in
Length	2.377 m   7.8 ft
Pipe Length	3,048 mm   120 in
Face Support Pipe Diameter	73.152 mm   2.88 in
Pipe Outer Diameter	73.152 mm   2.88 in

## Material Specifications

Material Type	Hot dip galvanized steel
---------------	--------------------------

## Mechanical Specifications

Wind Rating	For Specifications, please contact your local ANDREW representative
Wind Rating Test Method	TIA/EIA-222

## Packaging and Weights

Included	Ballast tray   Frame   Plain end pipes (4)
Packaging quantity	1
Weight, net	866 kg   1,909.201 lb

# RT-DF15-4-120

---

\* Footnotes

**Wind Rating**                      BWS—Base Wind Speed; FBC—Florida Building Code